







Techincal Specification Sheet

Aluminium Roller Shutter

ller Shutter



Product Specifaction / Features

Product Code: SS02
Max Width 5m
Max Height 5m
Weight per sqm 7.5

SS02

Lath Height/Profile 36, 55, 77mm

Single/Twin Skin? Twin

Material Aluminium

Guide Depth 25,45,53.60,65

Plate Size 150-300mm

Colours Available Full RAL

Punch/Perf Available? Yes



Additional Information

Why Aluminium Shutters?

Aluminium shutters are a great choice for any home or business owners who are looking for a sleek and cost-effective way to protect their property. Available in a range of colours and profiles, and designed with visual appeal in mind, they are a great option to use in places where discretion is key.

Due to their lightweight construction, they are easier to install and cheaper to produce than their steel counterparts, and can often be made to cover smaller openings.

There are 100's of colour options available with additional options such as safety edge sensors, punched/perforated lath, alarmed opening and closing, and fire resistance.

If you need a stylish solution for security or insulation without breaking the bank then look no further than an aluminium roller shutter.

Aluminium shutters are one of the most popular options for insulated garage doors, due to the light weight of the materials used, they can be supported without the need for heavy duty re-inforcements like steel or timber frameworks.

Perforated and punched finishes are available on non-insulated shutters, which help to enable airflow and visibility into and out of the premises. Shutters like this are them ideal for homes, shops, and other buildings with commercial applications where the free movement of air is necessary. Ask us about the following options:

- Powder coated (any colour desired).
- Flat lath
- Tube and link
- Perforated
- Punched

Due to the low melting point of aluminium, they are generally not suitable for fire-resistant applications. We do stock a wide range of fire shutters, so please take a look at our page concerning them.

Operation is available through electric motor (tubular or direct drive), or a counter balance spring for manual use. All electrically operated roller shutters can be fitted with any one of a variety of control options such as key switch, push buttons, remote control, keypad, and many more.

S&S Shutters Unit 530 Hertford Road, Edmonton, London, N9 8AE

0800 112 0083 | 0203 887 0993 | info@sandsshutters.net